

## **AMENDMENTS TO THE CLAIMS**

*The listing of claims will replace all prior versions and listings of claims in the application:*

### **Listing of Claims:**

1. (Currently Amended) A coupling unit, comprising:
  - a connecting area for connecting to a transmitting and/or receiving module;
  - a holding sleeve configured to receive an optical fiber within the holding sleeve; and
  - a transparent coupling area configured for directly contacting the optical fiber and for directly coupling light between the optical fiber and the optical transmitting and/or receiving module when the optical fiber is inserted into said holding sleeve and the optical transmitting and/or receiving module is connected to said connecting area; and  
a horizontally running base plate formed with said coupling area therein, said base plate having an upper face connected to said holding sleeve, a lower face connected to said connecting area, and a cutout passing through said base plate;  
said transparent coupling area formed integral with said holding sleeve and said connecting area.
2. (Previously Presented) The coupling unit according to claim 1, wherein:
  - said coupling area has a side facing said holding sleeve that forms a projecting stop surface for the optical fiber; and
  - said stop surface is for directly contacting a fiber core of the optical fiber when the optical fiber is inserted into said holding sleeve.
3. (Previously Presented) The coupling unit according to claim 2, wherein:
  - said holding sleeve defines a longitudinal axis; and
  - said stop surface runs at right angles to said longitudinal axis of said holding sleeve.

4. (Original) The coupling unit according to claim 1, in combination with the optical fiber, wherein:
  - the optical fiber has a refractive index; and
  - said coupling area has a refractive index matched to the refractive index of the optical fiber.
5. (Original) The coupling unit according to claim 1, wherein:
  - said coupling area has a side facing the transmitting and/or receiving module; and
  - said side facing the transmitting-and/or receiving module has an inclined light inlet or light outlet surface.
6. (Previously Presented) The coupling unit according to claim 1, wherein said transparent coupling area, said holding sleeve, and said connecting area form a transparent, plastic injection-molded part.
7. (Previously Presented) The coupling unit according to claim 1, further comprising:
  - a horizontally running base plate formed with said coupling area therein;
  - said base plate having an upper face connected to said holding sleeve;
  - said holding sleeve extending essentially at right angles with respect to said upper face of said base plate; and
  - said base plate having a lower face connected to said connecting area.
8. (Previously Presented) The coupling unit according to claim 1, wherein said holding sleeve forms an elongated sleeve with a precision guide.
9. (Previously Presented) The coupling unit according to claim 1, wherein said holding sleeve is designed for holding a ceramic ferrule having a center configured with the optical fiber.

10. (Original) The coupling unit according to claim 1, wherein said connecting area is essentially cylindrical.
11. (Original) The coupling unit according to claim 10, wherein said connecting area is designed for connecting to a TO can in which the transmitting and/or receiving module is configured.
12. (Currently Amended) The coupling unit according to claim 1, further comprising:  
~~a horizontally running base plate formed with said coupling area therein;~~  
~~said base plate having an upper face connected to said holding sleeve;~~  
said holding sleeve extending essentially at right angles with respect to said upper face of said base plate; and  
~~said base plate having a lower face connected to said connecting area;~~  
~~said base plate formed with a cutout passing through said base plate; and~~  
said cutout running adjacent said coupling area of said base plate.

13. (Currently Amended) A coupling unit comprising:
- a substantially cylindrical holding sleeve configured to receive an optical fiber within the holding sleeve;
  - a substantially cylindrical connecting area configured to receive an optical module within the connecting area, the connecting area further configured to optically align the optical module with the optical fiber when the optical fiber is inserted into said holding sleeve;
  - a coupling area configured to couple light between the optical fiber and the optical module when the optical fiber is inserted into the holding sleeve and the optical module is received within the connecting area, wherein the coupling area is formed integral with the holding sleeve and connecting area and a common axis is shared by the holding sleeve and the connecting area; and
  - a cutout through a base plate, wherein the cutout extends from the holding sleeve to the coupling area along side the coupling area.

14. (Canceled)

15. (Previously Presented) The coupling unit according to claim 13, wherein the holding sleeve, connecting area, and coupling area are made from a transparent plastic material using an injection-molding process.

16. (Previously Presented) The coupling unit according to claim 13, wherein the coupling area is transparent and has a refractive index substantially matched to a refractive index of the optical fiber.

17. (Previously Presented) The coupling unit according to claim 13, wherein the optical module is a TO can and the connecting area receives the TO can and the TO can is secured to inner walls of the connecting area.

18. (Previously Presented) The coupling unit according to claim 13, wherein said connecting area is substantially cylindrical and has an inner diameter that is sized to substantially conform to the outer diameter of the module.

19. (Previously Presented) The coupling unit according to claim 13, wherein:  
said coupling area has an inclined surface configured to reflect light away from both the module and the fiber.

20. (Canceled)

21. (Canceled)

22. (Canceled)